



STRATTON TABLE ASSEMBLY

Base Part Location and Verification

Location	Quantity	Description	QC Check
Base Box	4	"K" Shaped Legs	
Base Box	2	Notched Top Straps	
Base Box	1	3-1/2" capped cylinder	

Hardware List and Verification

Quantity	Description	QC Check
12	2" Lag Bolts	
8	Black Lag Bolts	
20	Flat Washers	
4 (Threaded into Legs)	Levelers	

QUALITY CONTROL CHECK PERFORMED BY: _____

ATTENTION  Do Not Assemble with Power Tools
--

ASSEMBLY INSTRUCTIONS:

- 1) TO START, ATTACH THE "K" SHAPED LEGS TO THE CAPPED CYLINDER USING THE 2" LAG BOLTS. THE "CAPPED" SIDE OF THE CYLINDER WILL BE FACING UP TOWARDS THE LONGEST PART OF THE "K" AND EVENTUALLY THE BOTTOM OF THE TABLE.
- 2) PLACE THE BASE RIGHT SIDE UP ON A FLAT SURFACE.
- 3) CROSS THE 2 NOTCHED TOP STRAPSTO FORM A PLUS (+) SIGN BY FITTING THE NOTCHES OF EACH TOGETHER. THE TOP STRAPS HAVE 4 HOLES DRILLED FOR ATTACHMENT TO THE BASE AND 8 COUNTERSUNK HOLES DRILLED FOR ATTACHING THE BASE TO THE TABLE TOP. WITH THE 8 COUNTERSUNK HOLES FACING DOWNWARD, ALIGN THE 4 HOLES OF THE TOP STRAPS WITH THE 4 HOLES OF THE "K" LEGS AND ATTACH WITH LAG BOLTS.
- 4) PLACE THE TABLE TOP FACE DOWN ON A SOFT NON-ABRASIVE SURFACE.
- 5) TURN THE BASE OVER AND ALIGN THE 8 COUNTERSUNK HOLES TO THOSE ON THE UNDERSIDE OF THE TABLE TOP AND ATTACH WITH THE **BLACK LAG BOLTS**. **IMPORTANT: BE CERTAIN TO USE THE BLACK LAG BOLTS, AS THE LONGER 2" LAG BOLTS MAY ACTUALLY GO THROUGH THE TABLE TOP.**

